



- Self-darkening helmet mask for semi-professional use. Suitable for all types of welding with external darkening adjustment (DIN 9 ÷ 13; light state = 4), it guarantees high performance in TIG (it darkens with currents lower than 5A) / MIG-MAG / MMA. Viewing area 93\*43mm, optical class 1/1/1/2.
- Light and comfortable, it is equipped with a cruise adjustment system for optimal comfort.
- The LCD liquid crystal filter automatically darkens when the welding arc strikes and quickly returns to the transparent state when it is turned off, eliminating the need to raise and lower the mask at each work break and therefore allowing you to operate with your hands free .
- External adjustment of the degree of darkening to adapt to different welding applications. Adjustment of sensitivity and dimming delay.
- "GRIND" mode: it blocks the darkening of the mask glass to be able to carry out grinding operations protected and in complete safety.

## TECHNICAL DATA

CODE	<b>804234</b>	LUMINOUS STATE	<b>4 DIN</b>	SENSORS	<b>2</b>
CODE	<b>804234</b>	VARIABLE STATUS	<b>9-13 DIN</b>	VIEWING AREA	<b>93x43 mm</b>
TIG	<b>&gt; 5A</b>	SWITCHING TIME LIGHT-DARK	<b>0,3 ms</b>	DIMENSIONS	<b>300x240x240 mm</b>
MIG - MAG	*	DELAY FROM DARK TO LIGHT STATE	<b>0,2 - 0,9 s</b>	WEIGHT	<b>0,410 kg</b>
MMA	*	OPTIC CLASS	<b>1/1/1/2</b>		
GRINDING	*	OPERATING TEMPERATURE (MIN-MAX)	<b>-5 /+55 °C</b>		

## OPTIONAL ACCESSORIES

### MASKS FILTERS AND ACCESSORIES

804406	MAGNIFYING LENS 1.5X 107,4x50,5MM
804407	MAGNIFYING LENS 2.0X 107,4x50,5MM
804408	MAGNIFYING LENS 2.5X 107,4x50,5MM

## DESCRIPTION

Automatic helmet mask ideal for MMA, MIG-MAG and TIG welding with external darkening adjustment (DIN 4/9 ÷ 13).

The LCD liquid crystal filter automatically darkens on striking the welding arc and quickly returns to its transparent status when the arc is switched off; eliminating the need to lift and lower the helmet on each work break and thereby allowing the operator to work with hands free.

Features:

- adjustable automatic darkening filter;
- transparent filter protection;
- TIG >5 A;
- grinding mode;
- solar cell operation;
- light and comfortable.

OPTIONAL:

external glass protection 95x115,5mm Kit 2 pcs cod.804312

internal glass protection 47x100mm Kit 2 pcs cod.804313

Sweatband Kit 2 pcs cod.804099.

## DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL