

Plastična spoj- nica gumenih crijeva

- Postojana na benzin, dizel gorivo, ulje, vodu od pranja, kočionu tekućinu, antifriz itd.
- Različite dimenzije i izvedbe od acetalne smole.

Ravna spojnica gumenih crijeva

Unutarnji Ø crijeva D_1	D_2	L_1	br. art.	JP/kom.
3	2,5	25	0500 250 1	25
4	2,7	35	0500 250 2	
5	3	45	0500 250 3	
6	4	49	0500 250 4	10
8	5,6	56	0500 250 5	
10	7	63	0500 250 6	

Ravni redukcijski nastavak

Unutarnji D_1	Ø crijeva D_3	D_2	L_1	br. art.	JP/kom.
4	3	2,5	30	0500 250 10	25
6	4		43,5	0500 250 11	
8	6	4	48	0500 250 12	10
10	8	5,6	53,5	0500 250 13	
			60,5	0500 250 15	

T - spojnica gumenih crijeva

Unutarnji Ø crijeva D_1	D_2	L_1	br. art.	JP/kom.
3	2,5	25	0500 250 28	25
4	2,7	35	0500 250 29	
5	3	42	0500 250 30	
6	4	50	0500 250 31	10
8	5,6	58	0500 250 33	
10	7	62,5	0500 250 34	

T - redukcijski nastavak

Unutarnji D_1	Ø crijeva D_3	D_1	D_2	D_4	L_1	br. art.	JP/ kom.
3	4	3	2,5	2,5	25	0500 250 18	25
4	6	4		4	35	0500 250 19	

